

OS-EL24ALP230VO + OS-EL24ALP230VI

Job Name:	Date:	
Location:	Approval:	
Engineer:	Construction:	
Submitted to:	Unit #:	
Submitted by:	Drawing #:	
Reference:		

KEY FEATURES:

- Inverter Technology
- Auto Swing
- Multiple Fan Sped
- Sleep Mode
- Led Display

•	_		


















OS-EL24ALP230VO + OS-EL24ALP230VI

Indoor Model			OS-EL24ALP230VI	
Power supply		V, Ph, Hz	208-230V, 1Ph, 60Hz	
Communication wiring			14AWG*4	
	Capacity	Btu/h	24,000(6,400~24,300)	
	Input	W	2,695(335~2,940)	
Cooling	Rated current	A	12.3(2.1~12.9)	
	EER/EER2	Btu/w	8.9	
	SEER/SEER2	Btu/w	16.7	
	Capacity	Btu/h	24,000(6,700~27,500)	
	Input	W	2,490(485~3,020)	
11aatina at 47 °F	Rated current	A	11.3(3.3~13.2)	
Heating at 47 °F	СОР	W/W	2.82	
	HSPF4/HSPF2-4		8	
	HSPF5/HSPF2-5		6.2	
		Qty	1	
Indoor fan motor		Input	89	
		RLA	0.45	
Indoor air flow (Turbo/Hi/Med/Lo) (No duct)		CFM	588.24/564.71/447.06/341.18	
ESP (range)		In.wg.		
Indoor noise level (Hi/Med/Lo)		dB(A)	46/40/33.5	
Dehumidification		L/H	6.89	
	Dimensions (WxDxH)	inch	40.94x8.66x12.87	
Indoor unit	Packing (WxDxH)	inch	44.09x15.94x12.40	
	Net/Gross weight	lbs	28.88/36.60	
Drainage water pipe diameter		inch	5/8"	
Refrigerant piping (Liquid side/Gas side)		inch	3/8"/5/8"	
Design pressure		PSIG	550/340	
Controller			RG57 remote	
Poom tomporature	Cooling	F	62~90	
Room temperature	Heating	F	32~86	





OS-EL24ALP230VO + OS-EL24ALP230VI

Outdoor Model			OS-EL24ALP230VO
Power supply		V, Ph, Hz	208-230V, 1Ph, 60Hz
Min. circuit ampacity		А	19
Max. fuse		А	30
	Model		KTM240D57UMT
	Туре		Twin-ROTARY
	Brand		GMCC
Compressor	Capacity	Btu/h	26,400
	Input	W	2,085
	Rated current (RLA)	А	14.25
	Refrigerant oil	OZ	VG74 22.7
	Qty		1
	Input	W	80
Outdoor fan motor	RLA	А	0.76
	Speed	r/min	810/720
Outdoor air flow (Max)		CFM	1,764.71
Outdoor noise level (Max)		dB(A)	59.5
Throttle type			Capillary
	Dimensions (WxDxH)	inch	35.04x13.46x26.50
Outdoor unit	Packing (WxDxH)	inch	39.17x15.67x29.13
Outdoor unit	Net/Gross weight	inch	97.88/104.50
- C.	Туре		R410A
Refrigerant	Precharge	ft	25
Additional charge for 1/4	4 inch liquid pipe	OZ	
Additional charge for 3/8 inch liquid pipe		OZ	0.32
Refrigerant piping	Liquid side/Gas side	inch	3/8"/5/8"
	Max. pipe length	ft	164.04
	Max. difference in level	ft	82.02
A maketa maketa mana a mad	Cooling	F	5~122
Ambient temperature	Heating	F	5 ~ 86











W	D	Н
40.94in	8.66 in	12.87 in











Outdoor Unit Dimensions (in)		
WxDxH			

40.94x8.66x12.87