



PACKAGED TERMINAL AIR CONDITIONER

with HEAT STRIP



olmo-comfort.com

PACKAGED TERMINAL AIR CONDITIONER

with HEAT STRIP



OLMO



Model			OS-MBW-09HS	OS-MBW-12HS	OS-MBW-15HS
Power Supply		V-Ph-Hz	208-230V-1Ph-60	208-230V-1Ph-60	208-230V-1Ph-60
Cooling	Capacity	Btu/h	9200/9000	12000/11800	14700/14500
	EER2	W/W	11.3	10.7	10.6
	Input	W	790/780	1080/1060	1390/1370
	Current	A	4.3/4.9	5.5/6.1	7.5/8.9
Heating (Heat Strip)	Rated Capacity	Btu/h	10900/8900	10900/8900	15000/12200
	Rated Input (Heater)	kW	3.5	3.5	5
	Rated Current	A	15.3/13.7	14.96/13.7	22.3/20.1
Refrigerant Type		Type	R32	R32	R32
		oz	15.16	15.16	21.51
Indoor Air Flow (Hi/Lo)		ft3/min	430.0/342.3	431.1/348.2	430.0/349.4
Indoor Noise Level (Hi/Lo)		dB(A)	50/49.5	52/51.5	51/50.5
Outdoor Air Flow (Hi/Lo)		ft3/min	467.7/394.1/333.5	424.7/360.6/296.5	544.1/485.3/424.1
Outdoor Side Noise Level (Hi)		dB(A)	63	67	65
Design Pressure (Lo/Hi)		PSI	300/580	300/580	300/580
Operation Temp	Indoor (cooling/heating)	°F	63°F-90°F/32°F-80°F	63°F-90°F/32°F-80°F	63°F-90°F/32°F-80°F
	Outdoor (cooling/heating)	°F	64°F-109°F/41°F-75°F	64°F-109°F/41°F-75°F	64°F-109°F/41°F-75°F
Dimension(WxDxH)		in	42x21x16	42x21x16	42x21x16
Packing (WxDxH)		in	44.5x25x19.3	44.5x25x19.3	44.5x25x19.3
Net/Gross Weight		lbs	97.0/105.8	103.6/112.4	105.8/114.6

Features:

- Remote Control Included
- Smart Connect Built-In
- Auto Defrost
- Dual Fan Speed
- Auto Restart Function
- LED Display
- Fresh Air Input
- Compatible with 24V Thermostat

