

OLMO



# THROUGH THE WALL AIR CONDITIONER



[olmo-comfort.com](http://olmo-comfort.com)

# THROUGH THE WALL AIR CONDITIONER

# OLMO



Model			OW-P08AC115WF	OW-P08HS115WF	OW-P12AC115WF	OW-P12AC230WF	OW-P14AC230WF	OW-P12HS230WF	OW-P14HS230WF
Power Supply	V-Ph-Hz		115V-1Ph-60	115V-1Ph-60	115V-1Ph-60	208/230V-1Ph-60	208/230V-1Ph-60	208/230V-1Ph-60	208/230V-1Ph-60
Cooling	Capacity	Btu/h	8300	8000	12000	12000/11700	14000/13600	12000/11700	14000/13600
	EER	W/W	3.11	3.13	3.08	3.08	2.78	2.98/2.95	2.86/2.84
	CEER	Btu/h/W	10.6	9.6	10.5	10.5	9.5	9.5	9.5
	Input	W	760	750	1140	1140/1110	1400/1360	1180/1160	1430/1400
	Current	A	7.8	9.4	11.3	5.6/6.3	7.0/7.7	6.5/7.0	7.9/8.5
	Standby Power	W	1.25	1.34	1.25	1.435	1.435	1.34	-
Heating	Rated Capacity	Btu/h	-	4200	-	-	-	10600/8600	10600/8600
	Rated Input (Heater)	W	-	1220	-	-	-	3450/2821	3450/2821
	Rated Current	A	-	11	-	-	-	15/13.5	15.0/14.0
Compressor	Type		ROTARY	ROTARY	ROTARY	ROTARY	ROTARY	ROTARY	ROTARY
	Rated Current (RLA)	A	5.10	5.10	7.30	4.18/3.85±3%	6.00/5.55±3%	4.18/3.85±3%	6.00/5.55±3%
	Locked Rotor Amp(LRA)	A	36	36	49	28.5±10%	34.5±10%	28.5±10%	34.5±10%
Refrigerant Type	Type		R32	R32	R32	R32	R32	R32	R32
	oz		10.93	11.99	17.28	16.58	17.99	17.28	19.40
Indoor Air Flow (Hi/Mi/Lo)	ft3/min		270.0/232.9/202.9	258.8/227.1/192.4	276.5/250.6/220.0	274.7/259.4/237.1	280.0/264.7/245.3	273.5/251.8/230.6	272.4/251.8/232.9
Indoor Noise Level (Hi/Mi/Lo)	dB(A)		55.6/52.4/49.5	58.7/55.4/52	59/56.8/55.3	60.2/59/57.5	60.5/59.5/58	61.8/60/58	62.3/61.2/59.8
Outdoor Air Flow (Hi/Med/Lo)	ft3/min		467.7/394.1/333.5	424.7/360.6/296.5	544.1/485.3/424.1	532.9/497.1/452.9	554.1/526.5/487.1	451.2/408.8/366.5	480.0/439.4/400.0
Outdoor Side Noise Level (Hi/Med/Lo)	dB(A)		63.6/59.4/55.9	63.5/59.7/55.9	68.7/65.3/62	68.3/66.7/63.9	69.9/68/65.9	65.4/63.2/61.1	69.8/67.2/64.8
Power Cord Length	ft		7.02	5.58	7.02	6.50	6.50	5.58	5.58
Control Type			Remote Control/ Smart Connect	Remote Control/ Smart Connect	Remote Control/ Smart Connect	Remote Control/ Smart Connect	Remote Control/ Smart Connect	Remote Control/ Smart Connect	Remote Control/ Smart Connect
Operation Temp	Indoor (cooling/heating)	°F	63-90/ -	63-90/ -	63-90/ -	63-90/ -	63-90/ -	63-90/ -	63-90/ -
	Outdoor (cooling/heating)	°F	64-109	64-109/23-75	64-109	64-109	64-109	64-109/23-75	64-109/23-75
Dimension(WxDxH)	in		24.21x20.28x14.53	24.21x20.28x14.53	24.21x20.28x14.53	24.21x20.28x14.53	24.21x20.28x14.53	24.21x20.28x14.53	24.21x20.28x14.53
Packing (WxDxH)	in		27.95x26.57x16.93	27.95x26.57x16.93	27.95x26.57x16.93	27.95x26.57x16.93	27.95x26.57x16.93	27.95x26.57x16.93	27.95x26.57x16.93
Net/Gross Weight	lbs		65.48/77.16	66.80/77.16	74.96/87.52	74.52/86.86	75.40/87.74	74.96/85.76	77.38/87.74

Model			OW-A08AC115WF	OW-A12AC115WF	OW-A12AC230WF
Power Supply	V-Ph-Hz		115V-1Ph-60	115V-1Ph-60	208-230V-1Ph-60
Cooling (Only)	Capacity	Btu/h	8000	12000	12000
	CEER	Btu/h/W	9.6	9.5	9.5
	Input	W	830	1270	1270
	Current	A	7.08	11.04	5.22-5.57
	Standby Power	W	1.5	1.5	1.5
	Type		ROTARY	ROTARY	ROTARY
Compressor	Rated Current (RLA)	A	5.4	7.9	4.18
	Locked Rotor Amp(LRA)	A	33	54	28.5
Refrigerant Type	Type		R32	R32	R32
	oz		11.28	17.63	17.98
Indoor Air Flow (Hi/Mi/Lo)	ft3/min		267.06/231.18/200.59	282.94/258.82/232.94	282.35/265.29/242.94
Indoor Noise Level (Hi/Mi/Lo)	dB(A)		56/52.5/49.5	59/56.8/55.3	60.2/59/57.5
Outdoor Air Flow (Hi/Med/Lo)	ft3/min				
Outdoor Side Noise Level (Hi/Med/Lo)	dB(A)		63.6/59.4/55.9	68.7/65.3/62	68.3/66.7/63.9
Power Cord Length	ft				
Control Type			Remote Control/ Smart Connect	Remote Control/ Smart Connect	Remote Control/ Smart Connect
Operation Temp	Indoor (cooling)	°F	63-90	63-90	63-90
	Outdoor (cooling)	°F	64-109	64-109	64-109
Dimension(WxDxH)	in		24.21x20.28x14.53	24.21x20.28x14.53	24.21x20.28x14.53
Packing (WxDxH)	in		28.27x26.897x16.93	28.27x26.897x16.93	28.27x26.897x16.93
Net/Gross Weight	lbs		63.03/75.29	72.97/85.05	73.19/85.12

## Features:

- Remote Control Included
- Smart Connect from Anywhere
- Comfortable Sleep Mode
- Auto Restart Function
- Multiple Fan Speeds
- Timer
- Self-evaporative System
- Compound Filter
- LED Display
- Fresh Air Input

Model: OW-TTWSLV

TTW Sleeve  
sold separately



For more information visit [olmo-comfort.com](http://olmo-comfort.com)

Manufacturer reserves the right to discontinue or change specifications at anytime without notice or incurring obligations.

©2024 All rights reserved