



MULTI-ZONE ***Multi SIERRA*** SERIES

WALL MOUNTED MULTI-ZONE MINI SPLIT SYSTEM



Indoor: 9K, 12K, 18K, 24K Btu/h
Outdoor: 18K, 24K, 36K, 42K Btu/h
Up to 22.0 SEER2 Rating

olmo-comfort.com



Multi-Zone Wall Mounted Units

OLMO Indoor



Features:

- Remote Control Included
- Smart Connect from Anywhere
- Comfortable Sleep Mode
- Turbo and Eco Modes
- Multiple Fan Speeds
- Timer
- Louver Auto Swing
- Self Clean Mode
- LED Display

Indoor Models		OS-M09SRW-230VI	OS-M12SRW-230VI	OS-M18SRW-230VI	OS-M24SRW-230VI
Power Supply	V-Ph-Hz	208/230V-1Ph-60	208/230V-1Ph-60	208/230V-1Ph-60	208/230V-1Ph-60
Cooling	Capacity	Btu/h	9000	12000	18000
Heating	Rated Capacity	Btu/h	9500	13000	19000
Output Power		W	25	25	35
Rated Current		A	0.11	0.11	0.17
Indoor Air Flow		CFM	341	365	647
Indoor Noise Level (Hi/Mi/Lo)		dB(A)	39/35/30	39/35/30	45/41/37
Net Dimensions (WxHxD)		in	32.02x10.75x8.13	37.38x10.75x8.13	48x12.63x9.25
Packing (WxHxD)		in	39.38x13.19 x6.38	39.38x13.19 x6.38	51.75x15.44x12.50
Net/Gross Weight		lbs	19.84 / 24.25	19.84 / 24.25	31.97 / 37.48
Refrigerant Piping	Liquid Side / Gas Side	in	1/4" / 3/8"	1/4" / 3/8"	1/4" / 1/2"
					3/8" / 5/8"

*Line Set adapters included in Outdoor Unit Box.



Multi-Zone Outdoor Units

OLMO Outdoor



Outdoor Models		V-Ph-Hz	OS-MSR18-230VO	OS-MSR24-230VO	OS-MSR36-230VO	OS-MSR42-230VO
Power Supply		208/230V-1Ph-60	208/230V-1Ph-60	208/230V-1Ph-60	208/230V-1Ph-60	208/230V-1Ph-60
Cooling	Capacity	Btu/h	18000	24000	32000	42000
	EER2	Btu/h	12.5	12.5	12.5	10.5
	SEER2	Btu/h	21.0	22.0	21.0	20.0
Heating	Rated Capacity	Btu/h	18000	24000	36000	42000
	HSPF2	Btu/h	9.50	9.05	9.00	8.95
	COP2	W/W	3.45	3.66	3.37	3.17
Minimum Circuit Ampacity	A	23	25	32.2	35	
Max Fuse	A	30	30	50	50	
Outdoor Air Flow (Hi)	CFM	1850	2350	3411	3411	
Outdoor Side Noise Level	dB(A)	55	59	59	63	
Outdoor Unit	Dimensions (WxHxD)	in	33.88x26.38x12.25	37.38x33x13.38	37.38x41.38x13.38	37.38x41.38x13.38
	Packing (WxHxD)	in	39x17.75x28.75	43.75x18.13x36.25	43.75x18.138x47.25	43.75x18.138x47.25
	Net/Gross Weight	in	116.8/125.6	158.7/169.5	188.5/220.5	198.4/224.5
Refrigerant Type/Quantity	oz	R410A/63.49	R410A/81.13	R410A/105.82	R410A/120	
Refrigerant Precharge	ft	50	75	98	98	
Refrigerant Piping	Liquid Side / Gas Side	in	1/4" / 3/8"	1/4" / 3/8"	1/4" / 3/8"	1/4" / 3/8"
	Max Refrigerant Pipe Length Each/Total	ft	82/164	66/197	66/246	66/262
Ambient Temperature	Outdoor (Cooling)	°F	14~114.8	14~114.8	14~114.8	14~114.8
	Outdoor (Heating)	°F	-13~75.2	-13~75.2	-13~75.2	-4~75.2



Multi-Zone Combinations

MULTI-ZONE *Multi SIERRA* SERIES

OS-MSR18-230VO

Up to 2 indoor units

2 ZONES

9	9
9	12
12	12

OS-MSR24-230VO

Up to 3 indoor units

2 ZONES

9	18
12	12
12	18
18	18

3 ZONES

9	9	9
9	9	12
9	9	18
9	12	12
9	12	18
9	18	18
12	12	12
12	12	18
12	18	18

4 ZONES

9	9	9	9
9	9	9	12
9	9	9	18
9	9	12	12
9	9	12	18
9	9	18	12
9	12	12	12
9	12	12	18
9	12	18	12
12	12	12	18

OS-MSR36-230VO

Up to 4 indoor units

3 ZONES

9	9	12
9	9	18
9	9	24
9	12	12
9	12	18
9	12	24
9	18	18
9	18	24
9	24	24
12	12	12
12	12	18
12	18	18
12	18	24
12	24	24
18	18	18
18	18	24

4 ZONES

9	9	9	9
9	9	9	12
9	9	9	18
9	9	9	24
9	9	12	12
9	9	12	18
9	9	12	24
9	9	18	18
9	9	18	24
9	9	24	24
9	12	12	12
9	12	12	18
9	12	12	24
9	12	18	18
9	12	18	24
9	18	18	18
12	12	12	12
12	12	12	18
12	12	12	24
12	12	18	18

5 ZONES

9	9	9	9	9
9	9	9	9	12
9	9	9	9	18
9	9	9	9	24
9	9	9	12	12
9	9	9	12	18
9	9	9	12	24
9	9	9	18	18
9	9	9	18	24
9	9	12	12	12
9	9	12	12	18
9	9	12	12	24
9	12	12	12	12
9	12	12	12	18
9	12	12	12	24
12	12	12	12	12

OS-MSR42-230VO

Up to 5 indoor units

3 ZONES

9	9	12
9	9	18
9	9	24
9	12	12
9	12	18
9	12	24
9	18	18
9	18	24
9	24	24
12	12	12
12	12	18
12	18	18
12	18	24
12	24	24
18	18	18
18	18	24

4 ZONES

9	9	9	9
9	9	9	12
9	9	9	18
9	9	9	24
9	9	12	12
9	9	12	18
9	9	12	24
9	9	18	18
9	9	18	24
9	9	24	24
9	12	12	12
9	12	12	18
9	12	12	24
9	12	18	18
9	18	18	18
12	12	12	12
12	12	12	18
12	12	12	24
12	12	18	18

